



Pipeline Specification Summary

WWP - HeavySound Pipeline

General Description:

The HeavySound Sweet Pipeline is an 8" Pipeline which transports High Pressure Dry Sweet Gas 21 Kilometers from 15-09-61-16W5 to the West Whitecourt Gas Plant at 2-17-60-15W5. Valve stations and Tie-in points are installed along the length of the pipeline, at several locations.

Pipeline Static Data:			
Medium:	High Pressure Dry Sweet Gas		
License Approval :	18865	License H2S :	0.0 %
Diameter :	8"	Length :	21.0 Kms.
M.O.P :	8830 Kpa.	Normal Operating Pres.	6500-7500 Kpa.
ANSI Rating :	600 RTJ		

Tie-In / ESD Locations:		
STN 01	15-09-61-16	Block Valve, Producer T/I
STN 02	05-08-61-15	Block Valve, Producer T/I
STN 03	12-05-61-15	Riser Only
STN 04	05-05-61-15	Riser Only
STN 05	03-32-60-15	Block Valve, Producer T/I
STN 06	02-17-60-15	Block Valve – Inlet Control Valve

Tie In Specifications

Section A: WELLSITE Requirements

Gas Quality – Piping Configuration, Equipment & Reporting	
Dehydration	Production Must be routed to downstream dehydration.
H2S Composition (Max.)	0.0%
Separation Equipment	2 Phase or 3 Phase
Condensate	Combined with Gas Stream or Tanked - Trucked
Water	Tanked - Trucked
Metering	EFM (Electronic Flow Measurement)
Fuel Gas – (Site Supplied)	Metered
Fuel Gas – (External Source)	Metered
SCADA	Required for all direct T/I's
Gas & Liquids Sampling	Required as per Manual requirements
Daily Reporting Method	SemCAMS SCADA, Customer SCADA, Fax, e-mail

Section B: DOWNSTREAM FACILITY Requirements**Gas Quality**

H2S Composition (Max.)	0.0%		
Temperature (Max)	50° Celcius		
Water Dewpoint (combined stream)	Required -10 C		
Condensate	Recombined or Tanked		
BS&W	Required		
Water	NONE - Tanked		
Methanol	YES - Inhibited MeOH		
Corrosion Inhibitor Injection	YES	Type:	Champion RU 196
Sulphur Dispersants - Solvents	NONE		
Operational Liquids	NONE (Cleaning Solvents/Hydro/PL Initial Batch...)		
Operational Gasses	NONE (Purge Gasses N2 / CO2 / Air / ...)		

Piping - Configuration & Equipment

Dehydration Type	Glycol or Mole Sieve		
Dewpoint Auto Shut-in / Recycle	Required	Set Point:	-10° Celcius
Dewpoint Analyzer	Required		
BS&W Analyzer	Required		
BS&W Auto Shut-in / Diversion	Required		
Metering – Gas Production	EFM		
Metering – Condensate Production	EFM		
Metering - Water	Not Required		
Metering – Fuel Gas (site supplied)	EFM Metered or Estimate		
Metering – Fuel Gas (external)	Not Required		
Compressor Recycle	Required – Pressure Control		
Flare & Recycle Connections	Upstream of Sales Meter		

SemCAMS SCADA:

Flow Measurement (Sales)	Required		
Remote ESD	Required (Supplied at tie-in location)		
Compressor Run Status	Required		
Dewpoint Analyzer Status	Required		

Section C: SemCAMS Pipeline T/I Point Requirements**Piping Configuration and Equipment**

Pipe Specification (above ground)	SemCAMS SP-60		
Pigging Facilities	Required		
ESD Valve	Required		
Check Valve	Required		
Drains & Vents	Required		
Cathodic Protection – Insulating Kit	Required	Type:	Pikotek
Future Connection	Required		
Corrosion Monitoring Coupon	Required		

SemCAMS SCADA:

Pressure	Required		
ESD Valve Position	Required (Open – Moving – Closed)		
Remote ESD	Required (SemCAMS Control)		
ESD – Local PSHH	Required	Set Pressure:	
ESD – Local PSLL	Required	Set Pressure:	
TEG Status	Required		